
**Matrox Imaging Library (MIL) 10 Update 65
Release Notes (MILirisGTR)
November, 2017
(c) Copyright Matrox Electronic Systems Ltd., 1992-2017.**

This document outlines what is new and explains the current limitations and particularities when using MIL with Matrox Iris GTR.

It also presents last-minute information that did not make it into the manual or on-line help. Note that this help file serves to complement your manual. The information found in this file overrides your formally documented material.

Contents

1. [Overview of functionality](#)
 2. [Behavior changes](#)
 3. [Known Limitations](#)
-

1. Overview of functionality

The MIL Reference in MIL Help now documents Matrox Iris GTR specific values in the Mdig and Msys functions.

The help for this product should be readily available, as installed boards are displayed by default. To display only the Matrox Iris GTR information in this help file, go to the Customize MIL Help section of Chapter 0: About MIL help. Select the **Matrox Iris GTR** option from the **MIL Systems** drop-down list. Unselect all others. Select the **Non-Matrox computer** option from the **Computer** drop-down list.

2. Behavior changes

MIL 10 Update 65

- MIL 10 Update 65 is a cumulative update, including all content from MIL 10 Update 28.
- Using **M_WHITE_BALANCE** with **M_ENABLE** for the first time after **MdigAlloc** now behaves as described in the MIL Help (i.e., it internally calculates the white balance coefficients). Also, inquiring **M_BAYER_COEFFICIENTS_ID** before enabling the white balance will return **M_NULL**, as described in the MIL documentation.
- **MdigControl** with **M_SOURCE_OFFSET_Y** or with **M_GRAB_SCALE_Y** now generates a MIL error if executed on a color sensor and **M_GRAB_SCALE_Y** is set to 0.5 and **M_SOURCE_OFFSET_Y** is not a

multiple of 4. This is a sensor limitation and the previous behavior was causing buffer corruption.

MIL 10 Update 28

- **MdigControl** with **M_GAIN** is a range from 0 to 255.
 - The default image orientation of an image grabbed using Matrox Iris GTR was set so that it is the same orientation as an image grabbed using Matrox Iris GT.
 - **MdigControl** and **MdigInquire** have two new control/inquire types: **M_FOCUS_PERSISTENCE** and **M_FOCUS_PERSISTENT_VALUE**. The **M_FOCUS_PERSISTENCE** control/inquire type can accept **M_DISABLE** (**M_DEFAULT**) or **M_ENABLE** as values. The **M_FOCUS_PERSISTENT_VALUE** control/inquire type can accept the same values as **M_FOCUS**. If **M_FOCUS_PERSISTENCE** is set to **M_ENABLE**, then **MdigAlloc()** initializes the auto-focus position, if present, to the position determined by **M_FOCUS_PERSISTENT_VALUE**.
-

3. Known Limitations

- DCFs are not supported.